

VIZRA-3X

19x39" (500x1000mm) 3.9mm
Indoor LED Video Panel



DVS

Key Features:

- High-Contrast Blackface LEDs
- Smart Module Calibration
- Integrated Climbing Handles
- Magnetic Alignment Assist
- Magnetic Front/Rear Service Modules
- Detachable Hot-Swap Power Supply Unit
- Universal, Cable-Free Modular Platform
- Cross-Compatible with 500x500mm Half Panel

Specifications:

Pixel Pitch: 3.91mm

LED Type: SMD2020 Blackface

Panel Resolution: 128x256px

Dimensions: 19.7" x 39.2" x 2.9"
(500 x 1000 x 73mm)

Weight: 26.8 lbs / 12.1 kg

Mounting Options: Fly / Ground Stack

Maximum Rigging Height (Flown): 12 Panels

Maximum Rigging Height (Ground Stack): 8 Panels

Curvature: +/- 0°, 3°, 5°

Serviceability: Front/Rear

Optical Ratings:

Brightness: 1,000~ NITS

Viewing Angle: 160° H | 160° V

Minimum Viewing Distance: 10' / 3M

Brightness Adjustment: 255 Steps

Grayscale: 16-Bit

Contrast Ratio: 8,000:1

Power / Connections:

Voltage: 120-240v AC

Maximum Power Consumption: 240W / 2.0A @ 120v

Average Power Consumption: 120W / 1.0A @ 120v

Power Connection: PowerCON TRUE1 In/Thru

Data Connection: EtherCON In/Thru

Control System:

Receiving Card: NovaStar A5S Plus

Refresh Rate: 7,680≥ Hz

Scan Rate: 1/16

Environmental:

Ingress Protection Rating: IP30

Operating Temperature: -4° ~ +122° F

Operating Life: 100,000 Hours

Certifications: cETLus, FCC, EMC, RoHS

